



GEO BASIN DATA SHEET

CONSTRUCTION

The Geo Basin is constructed from a laminated teak composite. It is secured to the wall by means of integral cantilever brackets and a timber wall plate. The wall itself must be flat, vertical and have either a solid timber or masonry structure to take screw fixings.

PLUMBING CONNECTIONS

Geo Basins are fitted with a standard chrome 1/4" PREFLO (chainless) waste compatible with standard basin traps. The waste is fitted in the centre of the basin. Generally, taps are wall mounted but there is sufficient depth at the back of the basin to accept some conventional tap styles. Overflows are not fitted as a standard item.

CARE & MAINTENANCE

All our bathroom products are polished with Timbertect Plus™. This is an epoxy resin sealant which sinks into the timber and fuses with it, forming an exceptionally tough layer which will not absorb stains and which is straightforward to clean with standard non-abrasive bathroom and kitchen cleaners. Products containing bleach should be avoided as they may lighten the timber unevenly. Further information on care and maintenance is provided with the basin.

™ Triple-C Products

OUR BASINS CAN BE MADE TO INDIVIDUAL SIZES.
PLEASE CONTACT US TO DISCUSS YOUR REQUIREMENTS

DIMENSIONS

Length	500mm	19.5"
Width	400mm	15.5"
External depth	150mm	6"
Internal depth	115mm	4.5"
Wall thickness	34mm	1 1/4"
Crated weight	12 kg	26lbs
Crated size	620x520x300	25x21x12"

